

DRYWALL MATERIAL BOQ & LOGISTICS SPECIFICATION

SerDrywall Engineering BOQ & Container Load Planning System

CONTAINER & TRUCKLOAD LOGISTICS SUMMARY

- 1x 40ft High Cube Container Payload: 24,800 - 26,500 kg net / 68 - 76 m³
- 1x Standard / Mega Truckload: 24,000 kg / 85 - 90 m³
- Consolidated Mixed Loading: Gypsum plasterboards, galvanized C/U studs, bugle screws, and joint compounds are consolidated in a single freight.

MATERIAL DESCRIPTION	TECHNICAL STANDARD	EXPORT PACKING	CONTAINER RATIO
Standard White Gypsum Board (BA13)	EN 520 Type A (12.5mm)	50 Sheets / Pallet (150 m²)	18 - 20 Pallets / 40ft HC
Moisture Resistant Green Gypsum Board	EN 520 Type H2 (12.5mm)	50 Sheets / Pallet (150 m²)	18 - 20 Pallets / 40ft HC
Fire Resistant Red Gypsum Board	EN 520 Type F (12.5mm / 15mm)	40 - 50 Sheets / Pallet	16 - 18 Pallets / 40ft HC
BoardeX® Exterior Sheathing Board	EN 15283-1 GM-F-H1-I	40 Sheets / Pallet (115.2 m²)	18 - 19 Pallets / 40ft HC
Galvanized CW/UW Wall Stud & Track	EN 14195 (0.50 - 0.60mm)	12-16 Pcs / Bundle (3.00 m)	Top-of-Pallet Consolidation
DERZTEK Joint Compound & SATENTEK Plaster	EN 13963 / EN 13279-1	25 kg Kraft Bag / Palletized	Palletized or Bagged Stowage

CFY Engineering Arch. Cons. Building Materials Industry & Trade Co. Ltd.
Head Office: Cevizli Mah. Orhan Gazi Cad. 24/B Maltepe / Istanbul, TURKEY
Plant: Gebze / Kocaeli | Mersin Logistics Hub | Ambarli / Izmir Seaport Exits
Web: www.serdrywall.com | Email: info@serprofil.com

Export Department WhatsApp Line:
+90 (505) 507 04 18
FOB Mersin / CIF Global Seaports Delivery